










Model	Digital Display	Flash Memory	2.0 USB	Water Resistant	Alarm	Ethernet Connectivity	Battery Operation	Probe	# of Channels	Temp./Pressure Ranges*	Accuracy	Humidity Range
<b>TEMPERATURE/HUMIDITY</b>												
TM320	✓	✓	✓		✓		✓		2	-20 to +70°C	±0.44°C/±2% RH	0 to 95%
TM325	✓	✓	✓		✓		✓	✓	2	-20 to +70°C	±0.44°C/±2% RH	0 to 95%
TM725	✓	✓	✓		✓	✓	✓	✓	2	-20 to +70°C	±0.44°C/±2% RH	0 to 95%
TP125			✓		✓		✓		2	-23 to +80°C	±0.44°C/±2% RH	0 to 95%
TP325	✓		✓				✓		2	-20 to +70°C	±0.5°C/ ±2% RH	0 to 95%
TK180							✓		2	-20 to +70°C	±0.7°C/±2% RH	0 to 95%
TK500							✓		2	-20 to +70°C	±1°C/±2% RH	0 to 95%
FH320	✓	✓	✓		✓				2	-10 to +40°C, 0 to +100°F, 0 to +50°C	±1°C/±2% RH	0 to 95%
FH325	✓	✓	✓		✓			✓	2	-40 to +40°C/F, -20 to +80°C/F, -40 to +140°C/F, 0 to +100°C/F, 0 to +150°C/F, 0 to +250°F, 0 to +300°F	±1°C/±2% RH	0 to 95%
<b>TEMPERATURE</b>												
SM300	✓	✓	✓		✓		✓		1	-20 to +70°C	±0.44°C	
SM320	✓	✓	✓		✓		✓	✓	2	-184 to +1093°C	±1°C	
SM325	✓	✓	✓		✓		✓	✓	2	-184 to +1093°C	±1°C	
SM420	✓	✓	✓		✓		✓	✓	1	-45 to +176°C	±0.28°C	
SM720	✓	✓	✓		✓	✓	✓	✓	1	-184 to +1093°C	±1°C	
SM725	✓	✓	✓		✓	✓	✓	✓	2	-184 to +1093°C	±1°C	
VFC320	✓	✓	✓		✓		✓	✓	2	-29 to +70°C	±1°C	
VFC325	✓	✓	✓		✓		✓	✓	2	-29 to +70°C	±1°C	
SP125			✓		✓		✓		1	-23 to +80°C	±0.7°C	
SP175			✓		✓		✓	✓	2	-150 to +1093°C	±1°C	
SP325	✓		✓				✓		1	-20 to +70°C	±0.67°C	
SK180							✓		1	0 to +43°C	±0.7°C	
SK500							✓		1	-20 to +70°C	±1°C	
FT300	✓	✓	✓		✓				1	-10 to +40°C, 0 to +100°F, 0 to +50°C	±1°C	
FT325	✓	✓	✓		✓			✓	2	0 to +100°F, 0 to +50°C/F, -25 to +125°F, -40 to +60°C/F, +50 to +100°F, -40 to +160°F, -20 to +80°C/F		
HT100/HT120/HT125				✓			✓	✓	1	-20 to +125°C	±1°C	
<b>PRESSURE</b>												
PR100				✓			✓			0 to 100 PSI	±1%	
PR300				✓			✓			0 to 300 PSI	±1%	
PR500				✓			✓			0 to 500 PSI	±1%	
PL100	✓	✓	✓	✓			✓			0 to 100 PSI	±1%	
PL300	✓	✓	✓	✓			✓			0 to 300 PSI	±1%	
PL500	✓	✓	✓	✓			✓			0 to 500 PSI	±1%	

\*All models operate between -4 to +110°F

# Chart Recorders

Model	Chart Diameter	Battery Operation	Remote Probe(s)	Digital Display	Alarms	Relay Contacts	Selectable Temp. Ranges	Temp./Pressure Ranges	Humidity Range	Accuracy	Selectable Recording Times
<b>TEMPERATURE/HUMIDITY</b>											
	<b>TH800</b>	8"	✓				✓	0 to +50°C (+32 to 120°F)	0-95% RH	±1°C/±2% RH	24 hr. & 7 day
	<b>TH801</b>	8"					✓	0 to +50°C, +32 to +120°F	0-95% RH	±1°C/±2% RH	24 hr. & 7 day
	<b>TH802</b>	8"			✓	✓	✓	+32 to 120°F, 0 to +50°C, +40 to +110°F, +5 to +40°C	0-95% RH	±1°C/±2% RH	24 hr., 7 day, & 31 day
	<b>TH803</b>	8"		1	✓	✓	✓	-20 to +120°F, -20 to +50°C, +40 to +110°F, +5 to +40°C, 0 to +185°F	0-95% RH	±1°C/±2% RH	24 hr., 7 day, & 31 day
	<b>TH805</b>	8"		1	✓	✓	✓	-20 to +120°F, -20 to +50°C, +40 to +110°F, +5 to +40°C, 0 to +185°F	0-95% RH	±1°C/±2% RH	24 hr., 7 day, & 31 day
	<b>TH621</b>	6"					✓	0 to 50°C, 32 to 100°F	0-95% RH	±1°C/±2% RH	24 hr. & 7 day
	<b>TH622</b>	6"					✓	0 to 50°C, 32 to 100°F	0-95% RH	±1°C/±2% RH	24 hr. & 7 day
	<b>TH623</b>	6"		1	✓	✓	✓	0 to 85°C (0 to 185°F), 0 to 100°F, 0 to 50°C/F, 0 to 185°C	0-95% RH	±1°C/±2% RH	24 hr. & 7 day
	<b>TH625</b>	6"		1	✓	✓	✓	0 to 85°C (0 to 185°F), 0 to 100°F, 0 to 50°C/F, 0 to 185°C	0-95% RH	±1°C/±2% RH	24 hr. & 7 day
<b>TEMPERATURE</b>											
	<b>KT800</b>	8"	✓	1			✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F		±1°C	24 hr. & 7 day
	<b>KT801</b>	8"		1			✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F		±1°C	24 hr. & 7 day
	<b>KT802</b>	8"		1	✓		✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F, 0 to +500°C/F		±1°C	24 hr., 7 day, & 31 day
	<b>KT803</b>	8"		1	✓	✓	✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F, 0 to +500°C/F		±1°C	24 hr., 7 day, & 31 day
	<b>KT804</b>	8"		1	✓	✓	✓	0 to +1000°C/F, 0 to +2000°F, -20 to +20°C/F, +20 to +100°C/F, +50 to +150°C/F		±1°C	24 hr. & 7 day
	<b>KT805</b>	8"		1	✓	✓	✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F, 0 to +500°C/F		±1°C	24 hr., 7 day, & 31 day
	<b>KT855</b>	8"		2	✓	✓	✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F, 0 to +500°C/F		±1°C	24 hr., 7 day, & 31 day
	<b>KT856</b>	8"		2	✓	✓	✓	0 to +100°C/F, -50 to +50°C/F, 0 to +250°C/F, 0 to +500°C/F		±1°C	24 hr., 7 day, & 31 day
	<b>KT621</b>	6"		1			✓	-50 to +50°C/F, 0 to ±50°C, 0 to ±100°C/F, 0 to +250°C/F, 0 to +500°F, 50 to +100°C/F		±1°C	24 hr. & 7 day
	<b>KT622</b>	6"		1	✓		✓	-50 to +50°C/F, 0 to ±50°C, 0 to ±100°C/F, 0 to +250°C/F, 0 to +500°F, 50 to +100°C/F		±1°C	24 hr. & 7 day
	<b>KT623</b>	6"		1	✓	✓	✓	-50 to +50°C/F, 0 to ±50°C, 0 to ±100°C/F, 0 to +250°C/F, 0 to +500°F, 50 to +100°C/F		±1°C	24 hr. & 7 day
	<b>KT625</b>	6"		1	✓	✓	✓	-50 to +50°C/F, 0 to ±50°C, 0 to ±100°C/F, 0 to +250°C/F, 0 to +500°F, 50 to +100°C/F		±1°C	24 hr. & 7 day
	<b>SK4*</b>	4"	✓					-30 to +50°C, 0 to +100°F, -20 to +120°F		±1°C	24 hr. & 7 day
	<b>SL4*</b>	4"	✓		✓			-30 to +50°C, +45 to +90°F, 0 to +100°F, -20 to +120°F		±1°C	24 hr. & 7 day
	<b>VFC21</b>	4"	✓		✓			-18 to +21°C		±1°C	7 day
	<b>SC3*</b>	3"	✓					-25 to 0°C, -15 to +10°C, -5 to +20°C, +10 to +35°C, +25 to +50°C		±1°C	24 hr. & 7 day
<b>PRESSURE &amp; UNIVERSAL</b>											
	<b>PR8*</b>	8"	✓					0 to 100 PSI, 0 to 200 PSI, 0 to 1000 PSI		±2%	24 hr. & 7 day
	<b>PW4*</b>	4"	✓					0 to 100 PSI, 0 to 150 PSI, 0 to 200 PSI, 0 to 300 PSI, 0 to 500 PSI		±2%	24 hr. & 7 day
	<b>ET855</b>	8"			✓			0.0 to +100.0, 0 to +1000, 0.0 to +14.0, 0.0 to +150.0, 0.0 to +200.0, 0.0 to +300.0, -10.0 to +10.0, -150.0 to +250.0		±3%	24 hr. & 7 day

\*Various models available for different ranges